



Dynolite Valve Guard

All-in-One Gasoline Additive

A top-performance, All-IN-ONE Gasoline treatment, providing Octane improvement (adds up to 4 octane numbers-40 points), ethanol protection, lead replacement and fuel system cleanliness & protection. A 250ml bottle treats 40 litres of the fuel.

Features & Benefits

- Adds up to 4 octane numbers (40 points) to unleaded fuel.
- Prevents valve seat recession when used with unhardened valve seats.
- Prevents detonation, hot spots & running on.
- Prevents fuel system corrosion / helps protect components.
- Combats the adverse effects of ethanol in fuel.
- Carburettor anti-icing formula.
- Contains anti oxidant to improve fuel life.
- Increases the power across the RPM range, reduces hazardous hydrocarbon emissions and helps to maintain a cleaner engine.

Key Applications

- For all Classic Engines previously requiring Lead Fuel and now running on unleaded fuel.
- Please visit our website for applications guide and more details.

Technical Characteristics

Appearance	Clear
Flash point, °C	77
Density, °C	0.809
Kinematic viscosity @ 40°C	2.8 mm2/s

Health & Safety

This Dynolite lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. For further guidance on Product Health & Safety refer to the appropriate Dynolite Safety Data Sheet.

Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Available sizes - 250 ML [GGL872202].