

DYNOLITE

EUROPE'S CLASSIC MOTOR OIL



Dynolite Classic 20W-50

Classic Light Engine Oil

A premium grade, universal mid-detergent classic engine oil with optimum wear protection and shear stability. This 20W-50 classic oil grade results in improved lubrication, reduced oil consumption and minimum deposits. Designed specifically for petrol and diesel fuelled classic vehicles manufactured between 1950 - 1985 and is also suitable for older vehicles where full-flow cartridge filters have been retro-fitted. Also suitable as engine & transmission oil in all BMC FWD vehicles.

Features & Benefits

Excellent Wear protection

This Oil contains optimal levels of ZDDP (Zinc dialkyldithiophosphate) that provides anti-wear protection and minimize lubricant breakdown.

Excellent Low Temperature pumpability

This oil provides excellent low temperature pumpability so that the oil flows freely and minimises wear at engine start-up, even at very low temperatures. Similarly, bearing and timing gear life is maximised due to this oil's excellent performance from cold start to the engine's full operating temperature range.

Resistance to Corrosion & Oxidation

The oil formulation has strong anti-corrosion as well as high resistance against oxidation. Reduces engine deposits to help maximise engine response.

Key Applications

- Designed specifically for petrol and diesel fuelled classic vehicles manufactured between 1950 – 1985.
- Also suitable for older vehicles where full-flow cartridge filters have been retro-fitted.
- Suitable as Engine & Transmission Oil in all BMC FWD vehicles, including Classic Minis.
- Please visit our website for applications guide and more details.

Approvals or Performance

- API: SG/CE

Technical Characteristics

SAE viscosity grade	20W-50
Density (20°C), g/cm ³	0.891
Flash point (COC), °C	235
Kinematic viscosity (40°C), mm ² /s (100°C), mm ² /s	160.5 18.2
Viscosity index	126
Pour point, °C	-25.0
ZDDP "Phosphorous"	760 ppm
ZDDP "Zinc"	835 ppm

Health & Safety

This Dynolite Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. For further guidance on Product Health & Safety refer to the appropriate Dynolite Safety Data Sheet.

Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Available sizes - 5 litres (GGL812150) and 1 litre (GGL812110).

09/2018