



Dynolite Shock Oil

Lever Arm & Piston Shock Absorber Oil

Premium suspension oil for simple or double action shock absorbers, in particular for "Armstrong" lever shock absorbers and motorbike forks. This oil contains anti-corrosion and anti-wear additives for enhanced protection.

Key Applications

- Recommended for simple or double action shock absorbers, in particular for "Armstrong" lever shock absorbers.
- Can also be used as a motorcycle fork oil where a heavy SAE 20 oil was originally specified.
- Not for use in vane type shock absorbers, for vane type use: Dynolite Transoil 140.
- Please visit our website for applications guide and more details.

Technical Characteristics

ISO Grade	68
Density (20°C), g/cm ³	0.881
Flash point (COC), °C	220
Kinematic viscosity (40°C), mm ² /s	68
(100°C), mm ² /s	8.70
Viscosity index	102
Pour point, °C	-24.0

Health & Safety

This Dynolite lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. For further guidance on Product Health & Safety refer to the appropriate Dynolite Safety Data Sheet.

Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Available sizes - 1 litre (GGL832110).